

Model 330 Controller Cabinet

Standard Features:

- Meets all N.Y.D.O.T. and FHWA requirements
- 8 phase, 4 ped, 2 overlaps operation
- 16 detector channel capability (2 per phase)
- 2 or 4 channel detector modules can be used (loop, magnetometer or magnetic)
- 2 R/R preemption inputs (AC isolation)
- 4 emergency vehicle inputs
- DC isolation inputs for pedestrian push buttons and special functions
- Programmable "yellow/red, or "all red" flash, or no flash for all loadswitch positions
- 210 monitor slot
- 1 dual circuit flasher position



Material	Aluminum (0.125"/0.188" thick)
Finishes	Natural, Painted, Anodized
Dimensions	51" H x 20" W x 18" D
Mounting	<u>Base Mounted</u> - (4) 3/4" x 16" Anchor
Bolts (optional)	
	<u>Side of Pole</u> - Brackets Optional
	<u>Pedestal</u> - Hardware Optional
Access	Full size front door
Ventilation	100 CFM Fan with Thermostatic Control Filtered air intake in door
Lock System	3 point, choice of Corbin or Best locks
Handles	Removable aluminum hex key
Door Stops	90 & 180 deg. stop, door top (+/- 10 degrees)
Cabinet Assembly	(1) Controller Shelf (1) 14-position Input File (1) Combined Loadswitch (14), Field Wire and Detector Termination Panel (7) Heavy Duty Transfer Relays (1) Power Distribution Assembly (1) 24V DC Power Supply (swing-out) (1) Police Panel w/ lights On/Off & Auto/Flash Switches (1) Fan & Thermostat Assembly (1) Current Monitor Panel (optional)
	Note: Standard subassemblies assure interchangeability between manufacturers.
Shipping Wt.	200 lbs., without plug-ins