

Model 337 Controller Cabinet

Standard Features

- Meets all City of Los Angeles and FHWA functional requirements
- 6 vehicle/pedestrian phases
- 11 slot input file
- Combined Power Distribution Assembly and 24V DC Power Supply
- 2 or 4 channel detector modules can be used (loop, magnetometer or magnetic)
- R/R Preemption (AC isolation)
- Emergency vehicle inputs
- DC isolation inputs for pedestrian push buttons and special functions
- Programmable "yellow/red" or "all red" flash (or no flash) through the use of flash plugs
- 210 monitor slot
- 1 dual circuit flasher position

Material	Aluminum (0.125" thick)
Finishes	Natural, Painted, Anodized
Dimensions	35" H x 20" W x 17" D
Mounting	<i>Top of Pole</i> - slipfitter for post-top mounting (optional) <i>Side of Pole</i> - 2 sturdy pole mounting brackets (optional) <i>Adapter Bases</i> available for base mounting
Access	Full size doors, front and back
Ventilation	100 CFM Fan with Thermostatic Control. Filtered air intake in front door
Lock System	3 point, choice of Corbin or Best locks
Door Stops	Two stops, each door, top
Rack Assembly	Standard, 19" EIA Rails, with: (1) Controller Shelf (1) 11 position input file (1) 6 position output file (3) Heavy Duty Transfer Relays (1) Combined Power Distribution Assembly and 24V DC power supply (1) Access to lights On/Off & Auto/Flash Switches through police panel opening (1) Fan & Thermostat Assembly

Note: Standard subassemblies assure interchangeability between manufacturers.

Shipping Wt. 130 lbs., without plug-ins or Model 170 Controller



Common Optional Features

- Fluorescent cabinet light(s) with door switch(es)
- Auto/manual control with police panel cord
- Communications panels
- Red monitoring kit
- Cabinet diagnostic kit on prom