## **SWARCO**

# McCAIN 343 CCTV CABINET



SWARCO McCain, Inc.'s 343 Closed Circuit Television (CCTV) Cabinet is a compact, and rugged pole-mounted cabinet for CCTV applications. This cabinet meets all Caltrans and Federal Highway Administration (FHWA) requirements. Convenient access to all interior assemblies and field terminations is available through two access doors. The cabinet is compatible with many types of sub-assemblies and comes equipped with a 19-inch Electronics Industry Alliance (EIA) rack. The McCain 343 CCTV cabinet shares many of the features of larger cabinets but with the added benefit of its small and compact design.



### **KEY BENEFITS**

- · Saves space with compact size
- · Incorporates standard 19-inch EIA rack
- · Comes with an easy and convenient pole mount
- Allows easy access to the cabinet's large inerior with front and back doors
- · Provides ventilation with filtered air

### PRODUCT DESCRIPTION

The McCain 343 CCTV Cabinet is an ideal cabinet for many CCTV applications. In addition to its easy side-of-pole mount, this cabinet is furnished with front and back doors making equipment installation a snap.


This cabinet is provided with a Field Termination Panel complete with four dual-row, 12-position, barrier-type terminal strips as well as AC neutral and ground bus bars providing ample room for all equipment connections.

A 6-position power strip, duplex receptacle, and duplex GFCI outlet also provide abundant means to power all the necessary equipment. A master 30 amp circuit breaker controls power to the cabinet. In addition, a radio interference filter/surge suppressor keeps unwanted electrical interference to a minimum.




# McCAIN 343 CCTV CABINET

FRONT



SIDE



### STANDARD FEATURES

- Standard 19" EIA rack
- Fluorescent cabinet lights (2), door switches (2)
- 30 amp main circuit breaker
- Surge arrestor and noise filter
- · Duplex receptacle, 20 amp
- GFI duplex receptacle, 20 amp
- Outlet strip, 6-position
- Shelf
- · Neoprene door gaskets

## ASSEMBLIES AND COMPONENTS

- Field panel
- Service panel

GENERAL SPECIFICATIONS	
Dimensions <sup>1</sup> :	24"W x 42"H x 20"D
Material:	5052-H32 aluminum, 0.125" thick
Finishes <sup>2</sup> :	Natural, anodized, or powder coated
Door:	Front door (1), back door (1), both full size
Latching System:	3-point, choice of Corbin or Best locks
Handles:	3/4" round, stainless steel, with padlock feature
Door Stops:	90° and 180° (±10°), each door, bottom
Rack Assembly:	Removable 19" EIA rack
Ventilation:	Thermostatically controlled 100 CFM fan, louvered air intake in door, pleated filter
Mounting:	Side-of-pole mounting
Shipping Weight <sup>3</sup> :	185 lbs

## **OPTIONS**

- External modems
- Pull-out drawer/shelf assembly



<sup>&</sup>lt;sup>1</sup>Dimensions rounded to the nearest inch

<sup>&</sup>lt;sup>2</sup>Powder coated options include standard, anti-graffiti, and custom colors

<sup>&</sup>lt;sup>3</sup>Without plug-ins or controllers